

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification ⁶ : H04M 3/42, 11/00	A1	(11) International Publication Number: WO 97/06625 (43) International Publication Date: 20 February 1997 (20.02.97)
(21) International Application Number: PCT/SE96/00947 (22) International Filing Date: 12 July 1996 (12.07.96) (30) Priority Data: 9502777-7 4 August 1995 (04.08.95) SE (71) Applicant (for all designated States except US): TELIA AB [SE/SE]; S-123 86 Farsta (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): ANDREASSON, Mikael [SE/SE]; Vänortsvägen 12; S-977 54 Luleå (SE). BODIN, Ulf [SE/SE]; Ljunggatan 2, S-973 31 Luleå (SE). BÄCKMAN, Mikael [SE/SE]; Havrevägen 6, S-954 32 Luleå (SE). (74) Agent: KARLSSON, Berne; Telia Research AB, Rudsjöterrassen 2, S-136 80 Haninge (SE).	(81) Designated States: NO, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.	

(54) Title: ARRANGEMENT FOR COMPUTER-CONTROLLED TELEPHONY AND PUBLIC SERVER IN ADDITION

(57) Abstract

The invention relates to an arrangement for computer-controlled telephony which includes a data terminal at a subscriber's which is intended to handle telecommunication services in a public telecommunication network. According to the invention a server is provided which belongs to or communicates with the public telecommunication network. The server includes an application program interface (API) and the subscriber's data terminal is connected to the server and can utilize the application program interface to handle the telecommunication services.

Owing to the server, the subscriber him/herself can control his/her service profile with different application programs. The invention also provides a server for use in the arrangement above. The server includes the application program interface which supports the communication between the data terminal and the telecommunication network and preferably storage for data and programs. The storage can be allocated individually to different subscribers for their own data and programs, at which the server provides processor capacity for execution of these programs. The invention is preferably implemented in an intelligent network IN by means of the protocol INAP.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

TITLE OF THE INVENTION: ARRANGEMENT FOR COMPUTER-CONTROLLED
TELEPHONY AND PUBLIC SERVER IN ADDITION

5
TECHNICAL FIELD

The present invention relates to an arrangement for computer-
controlled telephony, i.e. use of an intelligent terminal or
10 computer to control telephone services in a public telecommunication
network. The invention also relates to a public server which
includes an application program interface to make an effective and
new arrangement for computer-controlled telephony possible.

15
PRIOR ART

Integration of computers and telephones is today a field of current
interest, and activities are going on at a number of important
20 operators in the computer market. Several software suppliers of
personal computers have developed application program interfaces for
development of computer-controlled telephone services. Manufacturers
of PABXs (Private Automatic Branch Exchanges) offer interfaces
towards their exchanges for these application program interfaces,
25 which make possible development of advanced telephone applications
in PABX environment. An integrated system with connected PABX offers
complete computer telephone functionality, but more simple
applications can also be developed outside the PABX environment.
These applications then will have a restricted computer telephone
30 functionality.

In a near future personal computers will probably be a common
type of intelligent telephone terminals. Such a telephone terminal
will call for new demands on the public telecommunication networks,
which the telecommunication networks of today cannot fulfil.
35 Services in intelligent networks will not be possible to be utilized
to the full, because there is lacking a general interface to handle
services with computer control in an effective way. Within this
field a number of patent documents are known.

EP-A-0 629 091 shows a telecommunication system which supports a number of different user applications. According to the document, calls from a subscriber is connected to one and the same point, independent of which application that is concerned. After that a connection is established to a suitable server which can handle the application in question. By the described method a computer consequently can be connected to a suitable server.

EP-A-0 518 195 describes a system and a method which offers a platform independent application program interface. This means that the interface is independent of which communication protocol that is used at exchange of information between application programs.

EP-A-0 527 590 relates to connection of computers via ISDN for distributed handling of applications by means of application program interface.

The present invention implies an improvement by a server being provided in the public network which can provide an application interface which makes possible utilization of the telecommunication services.

SUMMARY OF THE INVENTION

Consequently the present invention provides an arrangement for computer controlled telephony, including a data terminal at a subscriber's. The data terminal is there to handle telecommunication services in a public telecommunication network.

According to the invention a server is provided which belongs to or communicates with the public telecommunication network and which includes an application program interface. The subscriber's data terminal is connected to the server and can utilize the application program interface to handle the telecommunication services. The data terminal can be connected via a separate data channel or via an open data network.

According to the invention there is also provided a public server for computer-controlled telephony in an arrangement of the type above. The server includes an application program interface which supports communication between the data terminal and the telecommunication network and a storage for data and programs. According to a preferred embodiment the storage can be arranged

individually for a subscriber for storing of his/her data and application programs.

The different aspects of the invention are defined in details in the enclosed patent claims.

5

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described in details with references to enclosed drawings, where

Figur 1 is a block diagram over the construction of an arrangement for computer-controlled telephony according to the present invention.

Figure 2 is a block diagram over the construction of the public server according to the present invention, and

Figure 3 is an example of implementation of the invention with the intelligent networks, IN, of today.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS OF THE INVENTION

As has previously been mentioned, integration of computers and telephones (Computer Telephone Integration, CTI) is a topic of current interest. Previously CTI-systems were implemented especially in PABX environment. According to the present invention the CTI-implementation is moved out from the PABX to the public telecommunication network owing to a new public telephone server (PTS).

With the PTS-concept according to the present invention we intend to offer a flexible platform for future telephone services adapted to intelligent telephone terminals of type personal computer with CTI-software. This platform principally consists of an application program interface API, which can be based on ECMA's CTI-recommendation CSTA. The subscribers have access to the application program interface via a separate data channel (data network), see Figure 1. The PTS concept consequently is aimed at subscribers with intelligent telephone terminals generally, and these intelligent telephone terminals can with advantage be of type personal computer.

The PTS-concept can be implemented with the IN-concept as base and then implies that the access to the IN-based services is made via a data channel instead of via tone signalling. IN-based services consequently will be offered as a standardized application program interface API, instead of completed services. By that a more flexible platform, a server PTS, which makes possible development of individually related services directly adapted to each separate subscriber's needs and wishes, is achieved. These services shall be possible to select to execute either in the subscriber's intelligent terminal, or in the server PTS.

Execution of services can be made either in the subscriber's intelligent terminal, or directly in the server PTS. Services which are executed in the subscriber's terminal utilizes the functionality in the application program interface of the server to obtain information from the telecommunication network, and to perform the operations which are wanted in the telecommunication network. The information is handled in the terminal, and the operations are initiated from the terminal.

Services can also be executed directly in the server PTS as an application program which also utilizes the application program interface API of the server. This program can be loaded down from the personal computer in order to make it possible for the subscriber to have access to PTS-based services and telephony, even if his/her intelligent terminal does not have active contact with the server PTS. This is necessary since PTS-based telephony implies that all incoming and outgoing calls are answered respectively initiated via the application program interface API of the server.

The PTS-concept requires that the subscriber has access to outband signalling, or a quite separate data channel beside its telephone connection. This data channel is used for the communication which is required between the subscriber's intelligent terminal and the application program interface API of the server to execute the application programs which the subscriber runs in his/her terminal or in the server PTS.

ECMA's (European Computer Manufacturers Association) CTI-recommendation CSTA (Computer Supported Telecommunications Application) defines the services which will constitute the base for the application program interface API of the server. These services are intended to be combined in an application program which performs

SUBSTITUTE SHEET

the wanted, individually related service. The subscriber has direct access to this application program interface AFI and can by that construct own unique individually related telephone services.

5 The server PTS consequently shall consist of three main parts which together constitute a server PTS. In certain cases it can be of current interest to introduce security aspects at access to the server PTS. An overall view of the architecture of the server PTS is shown in Figure 2.

10 There shall be an application program interface that shall offer possibilities to perform connections and to ask for information from the telecommunication network. This application program interface can be based on ECMA's CTI-recommendation CSTA. The application program interface of the server shall constitute an interface towards the telecommunication network and conceal which type of
15 network the server is connected to. This application program interface can utilize a communication protocol based on OSI protocol stack. The application program interface of the server will then be implemented on OSI layer 7 (Application layer). OSI layer 1-6 can be used for communication with the exchanges in the connected public
20 telecommunication network. Necessary security shall be built in in this application program interface to protect the underlying network from not allowed operations.

There shall be space for subscribers to store own data in the server. This storage shall be at the users disposal to store
25 application programs and other information which is related to these programs.

The server shall provide processor capacity for the subscribers to execute own application programs stored in the server. These programs utilize the application program interface of the server to
30 perform the intended individually related services which the subscriber wants.

The subscribers shall have possibility to reach the server from a data channel which can be an open data-communication network such as for instance Internet. If the connected data-communication network
35 is open (not private) a logging in procedure shall be performed where the identity of the subscriber is checked. In this case signalling and data exchange which is performed between the subscriber's intelligent terminal and the server shall be encrypted to guarantee the security at the transmission.

The server shall include both service related data and logic, as well as subscriber related data and logic. Service related data and logic is not dependent of any specific subscriber, but all subscribers will have access to the same data and logic.

Subscriber related data and logic is unique for each subscriber and each subscriber has only access to his/her own data and logic.

The application program interface of the server is intended to be a uniform interface to the functionality of which all subscribers have access. Application programs can by that be bought, be exchanged or be constructed by the subscriber which in this way can acquire his/her wanted service profile. The application program interface consequently will be the same for all subscribers and be realized by service related data and logic.

Security shall be built into the application program interface in order to prevent not allowed operations to be performed. Security which prevents that not allowed requests for information is made shall also be built into the application program interface. In addition there shall be a control mechanism in the application program interface which prevents that operations are performed in not allowed order, which can damage the underlying telecommunication network. These three aspects of security are the same for all subscribers and are realized by service-related data and logic.

Security shall be built into the application program interface to prevent that subscribers make connections or ask for information of not permitted type outside his/her own defined domain. A subscriber's domain is the connections and telephone numbers which are the subscribers own. A subscriber shall consequently be able to perform connections and ask for information without restrictions only within his/her own domain. This security is unique for each subscriber and is realized by subscriber-related data and logic.

The subscribers shall have possibility to load down application programs in the server to create own individually related services when the own intelligent terminal does not have contact with the server.

To run an application program in the server, the subscriber shall have access to a space of his/her own in the server where an application program of his/her own can be loaded down and also be executed. This space is realized by subscriber-related data and

logic. The processor capacity which is required to execute the programs is realized by service related data and logic.

The access to the server can be anticipated by a logging in procedure where the subscriber's identity is checked. The signalling and data exchange which is made between the subscriber's intelligent terminal and the server can be encrypted to guarantee the security at the transmission. This security is unique for each subscriber and is realized by subscriber-related data and logic.

With reference to Figure 1 is described how the invention can be implemented with the IN-concept as base.

In this implementation model, the server communicates directly with current SSF over IN's communication network with the communication protocol INAP (Intelligent Network Application Protocol). The telecommunication network will recognize the server as a type of SCF, since the telecommunication network only sees the server's INAP-protocol and has no knowledge of the other parts of the server. At incoming call to a subscriber which uses the invention, the SSF is detected that the telephone number is related to an IN-service. By that the information is asked for by an SCF which recognizes the number as a PTS-number. The control is handed over to the server to which the subscriber is connected. This delivery can be made via INAP. Please notice that the subscriber only has knowledge of and access to one server. The subscriber can after that handle the call via the application program interface of the server with his/her intelligent terminal. Alternatively the SSF can directly associate the call with right PTS which is preferred.

The model makes possible an effective realization of the invention and reuses the communication protocol INAP. By that the invention further develops the IN of today, and gives possibilities to develop individually related services.

The invention can of course be realized with a lot of equivalent softwares, which is realized by an expert in the field. The invention is only restricted by the following patent claims.

PATENT CLAIMS

1. Arrangement for computer-controlled telephony, including a data terminal at a subscriber, which data terminal is intended to handle telecommunication services in a public telecommunication network, characterized in a server (PTS) which belongs to, or communicates with, the public telecommunication network and which includes an application program interface (API), and that the subscriber's data terminal is connected to the server (PTS) and can utilize the application program interface (API) to handle telecommunication services.

2. Arrangement according to patent claim 1, characterized in that the data terminal is connected to the server (PTS) via a separate data channel or via out-band signalling.

3. Arrangement according to patent claim 1, characterized in that the data terminal is connected to the server (PTS) via an open data communication network.

4. Arrangement according to patent claim 3, characterized in that the access to the server (PTS) is controlled by a logging in procedure.

5. Arrangement according to any of the previous patent claims, characterized in that the server (PTS) communicates with an intelligent network (IN) by means of the communication protocol INAP.

6. Public server for computer-controlled telephony in an arrangement with a data terminal at a subscriber's, which data terminal is intended to handle telecommunication services in a public telecommunication network, characterized in an application program interface (API) which supports communication between the data terminal and the telecommunication network and a storage for data and programs.

7. Public server according to patent claim 6, characterized in that the application program interface (API) is based on CSTA.

8. Public server according to patent claim 6 or 7,
c h a r a c t e r i z e d in that a part of the storage can be
arranged individually to a subscriber for storing of his/her data
and application programs, and that the server (PTS) provides
5 processor capacity for execution of the subscriber's programs.

9. Public server according to any of the patent claims 6-8,
c h a r a c t e r i z e d in that security mechanisms which prevent
that not allowed information is requested by the telecommunication
network, and prevent not permitted operations and not permitted
10 sequences of operations.




Figure 1




Figure 2




Figure 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 96/00947

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04M 3/42, H04M 11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04M, H04L, G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	GB 2254981 A (GPT LIMITED), 21 October 1992 (21.10.92), page 3, line 18 - line 26; page 5, line 6 - page 6, line 5, figures 3,5 --	1-9
Y	EP 0479660 A2 (DIGITAL EQUIPMENT CORPORATION), 8 April 1992 (08.04.92), column 3, line 22 - column 5, line 11 --	1-9
A	EP 0384339 A2 (DIGITAL EQUIPMENT CORPORATION), 29 August 1990 (29.08.90), abstract --	1-9
A	WO 9517060 A1 (TALIGENT, INC.), 22 June 1995 (22.06.95), abstract --	1-9

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- * "A" document defining the general state of the art which is not considered to be of particular relevance
- * "E" earlier document but published on or after the international filing date
- * "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- * "O" document referring to an oral disclosure, use, exhibition or other means
- * "P" document published prior to the international filing date but later than the priority date claimed

* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

* "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

* "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

* "&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

31 October 1996

14.11.1996

Name and mailing address of the ISA:

Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Christian Rasch
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

01/10/96

International application No.

PCT/SE 96/00947

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB-A-	2254981	21/10/92	DE-A- 4212102	05/11/92
EP-A2-	0479660	08/04/92	CA-A- 2048306	03/04/92
			JP-A- 4230567	19/08/92
			US-A- 5475819	12/12/95
EP-A2-	0384339	29/08/90	AU-B- 611605	13/06/91
			AU-B- 630291	22/10/92
			AU-A- 4996190	13/09/90
			AU-A- 7603391	15/08/91
			CA-A- 2010762	24/08/90
			JP-A- 3116262	17/05/91
			US-A- 5341477	23/08/94
WO-A1-	9517060	22/06/95	AU-A- 7393294	03/07/95
			US-A- 5515508	07/05/96